









	
EVI DC Inverter Air Source Heat Pumps	
Model	<b>CGK025V3L</b>
Power Supply	220-240V~/50Hz
Heating Capacity Min./Max.	4.37/9.5kW
Heating Input Power Min./Max.	0.76/2.07kW
Cooling Capacity Min./Max.	2.85/6.2kW
Cooling Input Power Min./Max.	0.76/2.4kW
Rated. Input Power/Current	3kW/14.4A
Max. Water Outlet Temperature	55°C
Water Flow	1.6m <sup>3</sup> /h
Refrigerant/Weight	R32/1500g
Low/High side operation pressure	1.5/4.4MPa
Maximum allowable pressure	4.4MPa
Max Water Pressure	1.0MPa
Shock Proof Grade	I
WaterProof Level	IPX4
Water Pressure Drop	18kPa
Water Pipe Connection	1 inch
Net Weight	80kg
Date/NO.	See bar code
System CO2 equivalent charge weight: 1.01 ton	
Guangzhou Sprsun New Energy Technology Development Co., Ltd No. 15 Tangxi Road, Yinsha Industrial Park, Xintang, Zengcheng	



 	
EVI DC Inverter Air Source Heat Pumps	
Model	<b>CGK030V3L</b>
Power Supply	220-240V~/50Hz
Heating Capacity Min./Max.	5.52/12kW
Heating Input Power Min./Max.	0.99/2.7kW
Cooling Capacity Min./Max.	3.97/8.64kW
Cooling Input Power Min./Max.	1.09/3.44kW
Rated. Input Power/Current	3.9kW/18.7A
Max. Water Outlet Temperature	55°C
Water Flow	2.3m <sup>3</sup> /h
Refrigerant/Weight	R32/1700g
Low/High side operation pressure	1.5/4.4MPa
Maximum allowable pressure	4.4MPa
Max Water Pressure	1.0MPa
Shock Proof Grade	I
WaterProof Level	IPX4
Water Pressure Drop	20kPa
Water Pipe Connection	1 inch
Net Weight	88kg
Date/NO.	See bar code
System CO2 equivalent charge weight: 1.15 ton	
Guangzhou Sprsun New Energy Technology Development Co., Ltd No. 15 Tangxi Road, Yinsha Industrial Park, Xintang, Zengcheng	



 	
EVI DC Inverter Air Source Heat Pumps	
Model	<b>CGK-030V3L</b>
Power Supply	380-420V 3N~/50Hz
Heating Capacity Min./Max.	5.52/12kW
Heating Input Power Min./Max.	1.0/2.7kW
Cooling Capacity Min./Max.	3.97/8.64kW
Cooling Input Power Min./Max.	1.09/3.44kW
Rated. Input Power/Current	3.9kW/8.3A
Max. Water Outlet Temperature	55°C
Water Flow	2.3m <sup>3</sup> /h
Refrigerant/Weight	R32/1700g
Low/High side operation pressure	1.5/4.4MPa
Maximum allowable pressure	4.4MPa
Max Water Pressure	1.0MPa
Shock Proof Grade	I
WaterProof Level	IPX4
Water Pressure Drop	20kPa
Water Pipe Connection	1 inch
Net Weight	98kg
Date/NO.	See bar code
System CO2 equivalent charge weight: 1.15 ton	
Guangzhou Sprsun New Energy Technology Development Co., Ltd No.15 Tangxi Road, Yinsha Industrial Park, Xintang, Zengcheng	



 	
EVI DC Inverter Air Source Heat Pumps	
Model	<b>CGK-040V3L</b>
Power Supply	380-420V 3N~/50Hz
Heating Capacity Min./Max.	7.36/16kW
Heating Input Power Min./Max.	1.25/3.4kW
Cooling Capacity Min./Max.	4.8/10.44kW
Cooling Input Power Min./Max.	1.25/3.93kW
Rated. Input Power/Current	4.9kW/10.4A
Max. Water Outlet Temperature	55°C
Water Flow	2.7m <sup>3</sup> /h
Refrigerant/Weight	R32/2000g
Low/High side operation pressure	1.5/4.4MPa
Maximum allowable pressure	4.4MPa
Max Water Pressure	1.0MPa
Shock Proof Grade	I
WaterProof Level	IPX4
Water Pressure Drop	21kPa
Water Pipe Connection	1 inch
Net Weight	98kg
Date/NO.	See bar code
System CO2 equivalent charge weight: 1.35 ton	
Guangzhou Sprsun New Energy Technology Development Co., Ltd No. 15 Tangxi Road, Yinsha Industrial Park, Xintang, Zengcheng	



 	
EVI DC Inverter Air Source Heat Pumps	
Model	<b>CGK-050V3L</b>
Power Supply	380-420V 3N~/50Hz
Heating Capacity Min./Max.	9.2/20kW
Heating Input Power Min./Max.	1.55/4.2kW
Cooling Capacity Min./Max.	6.62/14.4kW
Cooling Input Power Min./Max.	1.7/5.36kW
Rated. Input Power/Current	6.1kW/12.9A
Max. Water Outlet Temperature	55°C
Water Flow	3.4m <sup>3</sup> /h
Refrigerant/Weight	R32/2800g
Low/High side operation pressure	1.5/4.4MPa
Maximum allowable pressure	4.4MPa
Max Water Pressure	1.0MPa
Shock Proof Grade	I
WaterProof Level	IPX4
Water Pressure Drop	23kPa
Water Pipe Connection	1 inch
Net Weight	124kg
Date/NO.	See bar code
System CO2 equivalent charge weight: 1.89 ton	
Guangzhou Sprsun New Energy Technology Development Co., Ltd No. 15 Tangxi Road, Yinsha Industrial Park, Xintang, Zengcheng	



 	
EVI DC Inverter Air Source Heat Pumps	
Model	<b>CGK-060V3L</b>
Power Supply	380-420V 3N~/50Hz
Heating Capacity Min./Max.	10.12/22kW
Heating Input Power Min./Max.	1.74/4.73kW
Cooling Capacity Min./Max.	7.29/15.84kW
Cooling Input Power Min./Max.	1.91/6.04kW
Rated. Input Power/Current	6.9kW/14.5A
Max. Water Outlet Temperature	55°C
Water Flow	3.8m <sup>3</sup> /h
Refrigerant/Weight	R32/2800g
Low/High side operation pressure	1.5/4.4MPa
Maximum allowable pressure	4.4MPa
Max Water Pressure	1.0MPa
Shock Proof Grade	I
WaterProof Level	IPX4
Water Pressure Drop	25kPa
Water Pipe Connection	1 inch
Net Weight	124kg
Date/NO.	See bar code
System CO2 equivalent charge weight: 1.89 ton	
Guangzhou Sprsun New Energy Technology Development Co., Ltd No. 15 Tangxi Road, Yinsha Industrial Park, Xintang, Zengcheng	



 	
EVI DC Inverter Air Source Heat Pumps	
Model	<b>CGK025V3L-B</b>
Power Supply	220-240V~/50Hz
Heating Capacity Min./Max.	4.32/9.4kW
Heating Input Power Min./Max.	0.76/2.06kW
Cooling Capacity Min./Max.	2.78/6.05kW
Cooling Input Power Min./Max.	0.74/2.44kW
Rated. Input Power/Current	3.09kW/14.79A
Max. Water Outlet Temperature	55°C
Water Flow	1.6m <sup>3</sup> /h
Refrigerant/Weight	R32/1500g
Low/High side operation pressure	1.5/4.4MPa
Maximum allowable pressure	4.4MPa
Max Water Pressure	1.0MPa
Shock Proof Grade	I
WaterProof Level	IPX4
Water Pressure Drop	18kPa
Water Pipe Connection	1 inch
Net Weight	78kg
Date/NO.	See bar code
System CO2 equivalent charge weight: 1.01 ton	
Guangzhou Sprsun New Energy Technology Development Co., Ltd No. 15 Tangxi Road, Yinsha Industrial Park, Xintang, Zengcheng	

 	
EVI DC Inverter Air Source Heat Pumps	
Model	<b>CGK030V3L-B</b>
Power Supply	220-240V~/50Hz
Heating Capacity Min./Max.	5.34/11.6kW
Heating Input Power Min./Max.	0.97/2.63kW
Cooling Capacity Min./Max.	3.43/7.46kW
Cooling Input Power Min./Max.	0.95/3.12kW
Rated. Input Power/Current	3.95kW/18.88A
Max. Water Outlet Temperature	55°C
Water Flow	2m <sup>3</sup> /h
Refrigerant/Weight	R32/1700g
Low/High side operation pressure	1.5/4.4MPa
Maximum allowable pressure	4.4MPa
Max Water Pressure	1.0MPa
Shock Proof Grade	I
WaterProof Level	IPX4
Water Pressure Drop	20kPa
Water Pipe Connection	1 inch
Net Weight	88kg
Date/NO.	See bar code
System CO2 equivalent charge weight: 1.15 ton	
Guangzhou Sprsun New Energy Technology Development Co., Ltd No. 15 Tangxi Road, Yinsha Industrial Park, Xintang, Zengcheng	

 	
EVI DC Inverter Air Source Heat Pumps	
Model	<b>CGK-030V3L-B</b>
Power Supply	380-420V 3N~/50Hz
Heating Capacity Min./Max.	5.34/11.6kW
Heating Input Power Min./Max.	0.97/2.62kW
Cooling Capacity Min./Max.	3.43/7.46kW
Cooling Input Power Min./Max.	0.95/3.11kW
Rated. Input Power/Current	3.94kW/8.31A
Max. Water Outlet Temperature	55°C
Water Flow	2m <sup>3</sup> /h
Refrigerant/Weight	R32/1700g
Low/High side operation pressure	1.5/4.4MPa
Maximum allowable pressure	4.4MPa
Max Water Pressure	1.0MPa
Shock Proof Grade	I
WaterProof Level	IPX4
Water Pressure Drop	20kPa
Water Pipe Connection	1 inch
Net Weight	88kg
Date/NO.	See bar code
System CO2 equivalent charge weight: 1.15 ton	
Guangzhou Sprsun New Energy Technology Development Co., Ltd No.15 Tangxi Road, Yinsha Industrial Park, Xintang, Zengcheng	

 	
EVI DC Inverter Air Source Heat Pumps	
Model	<b>CGK-040V3L-B</b>
Power Supply	380-420V 3N~/50Hz
Heating Capacity Min./Max.	7.27/15.8kW
Heating Input Power Min./Max.	1.26/3.42kW
Cooling Capacity Min./Max.	4.67/10.16kW
Cooling Input Power Min./Max.	1.24/4.05kW
Rated. Input Power/Current	5.13kW/10.83A
Max. Water Outlet Temperature	55°C
Water Flow	2.7m <sup>3</sup> /h
Refrigerant/Weight	R32/2000g
Low/High side operation pressure	1.5/4.4MPa
Maximum allowable pressure	4.4MPa
Max Water Pressure	1.0MPa
Shock Proof Grade	I
WaterProof Level	IPX4
Water Pressure Drop	21kPa
Water Pipe Connection	1 inch
Net Weight	98kg
Date/NO.	See bar code
System CO2 equivalent charge weight: 1.35 ton	
Guangzhou Sprsun New Energy Technology Development Co., Ltd No. 15 Tangxi Road, Yinsha Industrial Park, Xintang, Zengcheng	

 	
EVI DC Inverter Air Source Heat Pumps	
Model	<b>CGK-050V3L-B</b>
Power Supply	380-420V 3N~/50Hz
Heating Capacity Min./Max.	9.11/19.8kW
Heating Input Power Min./Max.	1.54/4.2kW
Cooling Capacity Min./Max.	5.86/12.74kW
Cooling Input Power Min./Max.	1.52/4.97kW
Rated. Input Power/Current	6.29kW/13.28A
Max. Water Outlet Temperature	55°C
Water Flow	3.4m <sup>3</sup> /h
Refrigerant/Weight	R32/2800g
Low/High side operation pressure	1.5/4.4MPa
Maximum allowable pressure	4.4MPa
Max Water Pressure	1.0MPa
Shock Proof Grade	I
WaterProof Level	IPX4
Water Pressure Drop	23kPa
Water Pipe Connection	1 inch
Net Weight	124kg
Date/NO.	See bar code
System CO2 equivalent charge weight: 1.89 ton	
Guangzhou Sprsun New Energy Technology Development Co., Ltd No. 15 Tangxi Road, Yinsha Industrial Park, Xintang, Zengcheng	

 	
EVI DC Inverter Air Source Heat Pumps	
Model	<b>CGK-060V3L-B</b>
Power Supply	380-420V 3N~/50Hz
Heating Capacity Min./Max.	10.03/21.8kW
Heating Input Power Min./Max.	1.74/4.72kW
Cooling Capacity Min./Max.	6.45/14.02kW
Cooling Input Power Min./Max.	1.7/5.59kW
Rated. Input Power/Current	7.08kW/14.94A
Max. Water Outlet Temperature	55°C
Water Flow	3.8m <sup>3</sup> /h
Refrigerant/Weight	R32/2800g
Low/High side operation pressure	1.5/4.4MPa
Maximum allowable pressure	4.4MPa
Max Water Pressure	1.0MPa
Shock Proof Grade	I
WaterProof Level	IPX4
Water Pressure Drop	25kPa
Water Pipe Connection	1 inch
Net Weight	124kg
Date/NO.	See bar code
System CO2 equivalent charge weight: 1.89 ton	
Guangzhou Sprsun New Energy Technology Development Co., Ltd No. 15 Tangxi Road, Yinsha Industrial Park, Xintang, Zengcheng	